



HUNTER

EXPLORER

2016 TRANSITION FROM WORK TO PLAY



info@africantusk.co.za | www.africantusk.co.za | +27 (0)44 343 1021

Made in South Africa

LEMAITRE QUALITY ASSURANCES

Due to the highly divergent nature of the work environment, it is impossible to issue a blanket, indefinite & unconditional guarantee on safety footwear. An all-encompassing guarantee would invite abuse from unscrupulous sectors. Instead, each claim is individually assessed to determine whether or not the footwear has provided the wearer "fair wear" within his or her specific work environment.

Lemaitre, being an SABS / ISO approved manufacturer, accepts full responsibility for unprovoked footwear faults, arising from material or manufacturing error.

In instances of doubt, the following limitations will be borne in mind:

- **Water** – Polyurethane/Leather footwear is water-resistant, not waterproof. In areas where there is constant exposure to water, employees should wear gumboots.
- **Oil** – Polyurethane-soled footwear is resistant to fuel and oil. The life of footwear will be prolonged if excess oil is regularly removed from the leather surface.
- **Acids** – Polyurethane exhibits good resistance to a broad spectrum of acids, providing that they are reasonably diluted. Concentrated hydrochloric, sulphuric and nitric acids will attack leather and most metals, so it is unreasonable to expect polyurethane to endure prolonged contact with them. [See the Polyurethane Chemical Resistance Table on www.bagshaw.co.za]
- **Heat** – The sole of Lemaitre polyurethane footwear is resistant to temperatures up to 90 degrees Celsius (not the uppers). Specialised heat-resistant footwear is required for environments exceeding 90 degrees Celsius.
- **Mines** – Lemaitre safety footwear is well suited for work on open-cast mines. However, when worn underground, PU footwear could constitute a hazard when it catches fire as it will give off a noxious gas. It should therefore be worn with circumspection.
- **Cement** – Cement, in conjunction with water, dehydrates the leather of safety footwear, hardening it and ultimately corroding the PU sole. However, PU footwear still acquits itself well on construction sites.

All reasonable claims for faulty footwear will be met, but in any instances of disagreement or dispute, the matter shall be settled by discussions between Bagshaw Footwear and the customer or, failing which, by referral to the South African Bureau of Standards in Pretoria.



SABS ISO 9001 CERTIFIED

LEMAITRE SOLE UNITS

PARABOLIC – COMFORT:

The parabolic sole is designed to provide the user with extra comfort. The thickness of the polyurethane (PU) midsole ensures excellent comfort, while the parabolic curve in the sole adds "spring" by absorbing the pressure of the person's mass. Discomfort is eliminated by the deep cleats and air movement channels preventing heat dissipating into the footwear through the sole. A slight shift in the body weight causes the parabolic sole to move air through the channels. Good "ladder grips" allow practical use of the footwear. The footwear, with an extra wide and extra high toecap, suits SA conditions.

MAXECO – GENERAL USE:

The Maxeco sole unit is designed for general use and applications, and has the added feature of built-in arch support for long hours on your feet. A large percentage of "surface contact" area offers superior slip resistance, with a geometrically designed "tread pattern" to displace water under the footwear in wet conditions. The footwear, with a wide toecap, suits SA conditions.

APOLLO – SLIP RESISTANCE:

The Apollo sole unit is specifically designed for maximum slip resistance. This sole unit is designed to provide maximum surface contact, and the square cleat edges and flow lines in the cleat design can traverse any surface area to maximise the slip resistance effect. The footwear, with a wide toecap, suits SA conditions.

RAPTOR – TORSION CONTROL:

This innovative and ground-breaking sole construction has a thermoplastic polyurethane (TPU) plate designed around the pressure points exerted on the arch of the foot. The TPU plate also gives maximum support to the ankle muscles in instances when the ankle could be twisted or sprained. The footwear, with an extra wide toecap, suits SA conditions.

LEMAITRE FOOTWEAR

Lemaitre Footwear bears the SANS quality mark as well as the ISO 9001: 2011 Quality Management Systems certification, which are applied during manufacturing. Specification is SANS 20345:2011 - Boots and Shoes with Direct Injection-moulded Soles.

Materials:

Genuine leather uppers • Anti-static insoles and socks • Optional steel toecap withstands 200 J • Optional stainless steel midsole withstands 130 kg nail-driven force • Double density polyurethane (PU), with special anti-static properties.

NB: As flexing, contamination, damage and wear can cause changes in electrical resistance, regularly check the sole. Should any new footbed inners be added, these should be checked for anti-static properties prior to insertion.

Care of Footwear

Regular maintenance of your footwear is important • Regularly remove all dirt with a moist cloth and then apply a good quality wax shoe polish • After use, the footwear should be kept in an open, well ventilated room • Allow wet footwear to dry slowly; never place near a heater or central heating element • Change footwear regularly, as leather is a natural product and should be allowed to rest • Wear cotton or natural fabric socks.

Wide Toecap

Lemaitre Footwear is fitted with wide fitting toecaps for South African conditions.

Storage

Never store footwear for extended periods • Polyurethane is a "green product" and will decompose through a process called hydrolysis, if stored in warm, damp and dark areas for extended periods.

Benefits of double-density polyurethane soles are:

The high-density PU sole layer is highly abrasion resistant. Due to its high impact absorption properties, the low-density PU midsole will give a high degree of comfort. The PU sole is oil and petrol resistant. PU has a lightweight advantage over other soling materials. The sole pattern ensures a non-slip grip on most surfaces.

PARABOLIC

Odyssey
Style No: 8000
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Nomad
Style No: 8001
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Quest
Style No: 8002
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Explorer
Style No: 8004
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Hunter
Style No: 8006
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Outeniqua
Style No: 8013
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

Maluti
Style No: 8016
SANS 20345



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Parabolic Sole Unit

LEMAITRE

APOLLO

NTC Clog
Style No: 8007
STC Clog
Style No: 8008
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-12
Sole : Apollo Sole Unit

Striker
Style No: 8037
SANS 20345

M



Toecap : Wide Steel Toecap 200j
Sizes : 5-12
Sole : Apollo Sole Unit

Eros
Style No: 8010
SANS 20345

M



Toecap : Wide Steel Toecap 200j
Sizes : 5-12
Sole : Maxeco Sole Unit

Maxeco
Style No: 8031
Maxeco SMS
Style No: 8011
Trojan NTC
Style No: 8060
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-13
Sole : Maxeco Sole Unit

Security Boot NTC
Style No: 8040
Security Boot STC
Style No: 8041
Security Boot STC SMS
Style No: 8042
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-12
Sole : Apollo Sole Unit

Sport
Style No: 8050
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-12
Sole : Apollo Sole Unit

Turtle
Style No: 8032
SANS 20345

M



Toecap : Wide Steel Toecap 200j
Sizes : 5-12
Sole : Maxeco Sole Unit

Chainsaw
Style No: 8033
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 3-13
Sole : Maxeco Sole Unit

Team
Style No: 8090
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-12
Sole : Apollo Sole Unit

Galaxy
Style No: 8095
Galaxy tan NSTC
Style No: 8096-03
SANS 20345

M



Toecap : Wide Steel Toecap 200j
Sizes : 5-12
Sole : Apollo Sole Unit

Metaguard
Style No: 8061
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 3-13
Sole : Maxeco Sole Unit

Robust
Style No: 8102
Frontier NTC
Style No: 8091
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-13
Sole : Maxeco Sole Unit

Taurus
Style No: 8506
SANS 20345

L



Toecap : Wide Steel Toecap 200j
Sizes : 2-9
Sole : Apollo Sole Unit

Limpopo
Style No: 8560
SANS 20345

U



Toecap : Wide Steel Toecap 200j
Sizes : 2-12
Sole : Apollo Sole Unit

Zeus
Style No: 8117
Zeus NTC
Style No: 8118
SANS 20345

M



Toecap : Wide Steel Toecap 200j
Sizes : 5-12
Sole : Maxeco Sole Unit

MAXECO

RAPTOR

Hawk
Style No: 8024

Hawk SMS
Style No: 8034
SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Eagle
Style No: 8025

Eagle SMS
Style No: 8035
SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Falcon
Style No: 8026

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Vulture
Style No: 8029

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Kite
Style No: 8044

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Owl
Style No: 8045

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Condor
Style No: 8047

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Hercules NTC
Style No: 8048

Hercules STC
Style No: 8049
SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Sentinel
Style No: 8072

SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

Hiker NTC
Style No: 8079

Hiker STC
Style No: 8039
SANS 20345

M



Toecap : Extra Wide Steel Toecap 200j
Sizes : 5-12
Sole : Raptor Sole Unit

L
LADIES

M
MENS

U
UNISEX

SMS

Steel Mid Soles available on certain non std styles as made to order only

NTC
No Toecap

STC
Steel Toecap